

Promatect LS suppliers UK – Smoke Control Dampers

- ⑥ Reinforcing strips of fire rated PROMATECT®-LS board d = 35 mm or equivalent

**Alternatives to Promatect LS 35
Promatect AD or
Promatect L500**

Else Minimum requirements of alternative material are

Density =	500 kg/m ³
Max thermal conductivity	0.09 w/m K
Compression strength min	5,5 N/mm ²
Flexural strength min	3 N/mm ²
Thickness min	40mm
Non-combustible acc.	DIN 4102 (A1)

Cut to size Promatect L500-35 can be sourced from

Johnsons Insulation Supplies Ltd
Johnsons House
16 Victoria Way
Burgess Hill
West Sussex
Tel : 01444 243 133
Contact Paul Johnsons
Email sales@jisltd.com

PROMATECT L500 uncut board available from
NDI,

Unit 2, Bilton Road,
Denby East, Bletchley,
Milton Keynes, MK1 1HW
- Telephone No: 01908 640634
- Email: miltonkeynes@ndi.co.uk

Encon Insulation,

Unit 13, Willie Snaithe Road,
Studlands Park Industrial Estate,
Newmarket,
Suffolk, CB8 7AU
- Telephone No: 01638 667208
- Fax No: 01638 664081
- Email: Newmarket@encon.co.uk

CCF Ltd, Unit 22,

Fison Way,
Fison Way Industrial Estate,
Thetford, IP24 1HJ
- Telephone No: 01842 766316
- Fax No: 01842 753728
- Email: ccfthetford@ccfltd.co.uk

PROMAT

Contact for all Promat material and cut to size pieces

Nicolas Molina - Segment Manager - OEM

M +44 7880 266065

E nicolas.molina@etexgroup.com

Promat UK Limited
Unit B1 Broadlands
Heywood Distribution Park
Pilsworth Road
Heywood
United Kingdom
OL10 2TS